



PRODUCT BULLETIN

SYNAVEX™ Full Synthetic 75W-90 Limited Slip Gear Oil

API GL-5

PRODUCT #501

CAM2 SYNAVEX™ Full Synthetic 75W-90 LS Gear Oil is a full synthetic heavy duty extreme pressure multi-grade gear oils manufactured with the highest quality synthetic base oil.

CAM2 SYNAVEX™ Full Synthetic 75W-90 LS Gear Oil, through the combination of naturally high viscosity index (low pour) synthetic base oils and up-to-date additive technology, are more economical than oils of lesser quality and lower initial cost. Using **CAM2 SYNAVEX™ Full Synthetic 75W-90 LS Gear Oil** may allow longer drain intervals, extended equipment life, and a significant reduction in maintenance cost and downtime.

FEATURES:

CAM2 SYNAVEX™ Full Synthetic 75W-90 LS Gear Oil delivers value through:

- **Excellent anti-wear Performance**
- **Limited Slip (LS) Performance**
- **Excellent anti-foam protection**
- **Outstanding seal compatibility**
- **Excellent shear stability**
- **Excellent Extreme Pressure Performance**
- **Exceptional thermal & oxidation stability**
- **Excellent rust and corrosion protection**
- **High Viscosity Index and Low Pour**
- **Excellent load carrying ability**

See Technical Data on pg 2.



CAM2 INTERNATIONAL, LLC

211 Violet Street, Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com



PRODUCT BULLETIN

SYNAVEX™ Full Synthetic 75W-90 Limited Slip Gear Oil

API GL-5

PRODUCT #501

APPLICATIONS

CAM2 SYNAVEX™ Full Synthetic 75W-90 LS Gear Oil may be recommended for the following applications:

- When API MT-1 gear oils are required
- When API GL-5, GL-4 gear oils are required
- When J2360, MIL-PRF-2105E or MIL-L-2105D are required
- When AIST Classification (formerly U.S. Steel 224) gear oils are required
- When Mack GO-G, GO-H AND GO-J gear oils are required
- When ArvinMeritor O76-E (Rockwell International) gear oils are required
- When AGMA 9005-E02, 250.03, 250.04, 251.02, No.4 gear oils are required
- In all Hypoid differentials, Automotive axles, Manual transmissions, Truck axles and Hubs
- In all lower units in Marine Outboard/Outdrive

TECHNICAL DATA

SAE GRADE	75W-90	75W-140
Product Code	501	547
API Classification	GL-5	GL-5
AGMA Grade	4	4.0-6.0
Viscosity @ 100°C, cSt	17.3	24.1
Viscosity @ 40°C, cSt	126	175
Viscosity Index	151	170
Gravity, API	31.2	33.1
Pour Point, °C(°F)	-48 (-54)	-48 (-54)
Channel Point, °C(°F)	<-51 (<-60)	<-51 (<-60)
Foam Test	Pass	Pass
Limited Slip	Yes	Yes

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC

211 Violet Street, Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com