



Product Data Sheet

Choice Gear 85W-140

Gear Oil

PRODUCT DESCRIPTION

Choice Gear 85W-140 oil is a premium quality transmission oil blended from highly refined high Viscosity Index base stocks. Through the combination of highly refined base oils and up-to-date additive technology, Choice Gear 85W-140 is more economical than oils of lesser quality and lower initial cost. Equipment life may be longer and more trouble-free, and maintenance cost and downtime may be significantly reduced through the use of Choice Gear Oils in conjunction with a dedicated preventive maintenance program.

Choice Gear 85W-140 is available to comply with most automotive and truck applications. Equipment manufacturer recommendations and conventional guides to lubricant selection should be followed to determine the best applications.

APPLICATIONS

Choice Gear 85W-140 may be recommended for the following applications:

- When API GL-5, GL-4 or GL-3 gear oils are required
- When MANN 342M-2 gear oils are required
- When MIL-L-2105D gear oils are required
- In all domestic automobile differentials and some manually shifted transmissions
- In oil lubricated wheel bearings
 - * Always consult your owner's manual for recommendations.

FEATURES AND BENEFITS

Choice Gear 85W-140 contains additive systems which impart characteristics most desired in these types of lubricants:

- Excellent chemical stability
- Excellent anti-foam protection
- Excellent thermal stability
- Excellent load-carrying ability

- Excellent rust protection
- Excellent oxidation resistance
- Excellent corrosion protection
- Excellent sludge formation resistance

TYPICAL PROPERTIES

SAE GRADE:	85W-140
Viscosity, cP @ C	60,000(-12)
Viscosity, cSt @ 40°C	375
Viscosity, cSt @ 100°C	26.5
Viscosity Index	95
Gravity, API	25
Pour Point, °C(°F)	-15(+5)
Channel Point, °C(°F)	-23(-9)

HEALTH AND SAFETY INFORMATION

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet.