

Product Data Sheet

Choice Heavy Duty 15W-40 CJ-4

Synthetic Blend Engine Oil

PRODUCT DESCRIPTION

Choice Heavy Duty 15W- 40 CJ-4 is formulated to provide the highest levels of equipment protection available through the use of premium quality Group II & Group III base stocks and up-to-date additive technology. Choice Heavy Duty 15W- 40 CJ-4 is a synthetic blend engine oil with next generation soot control.

Choice Heavy Duty 15W- 40 CJ-4 meets and exceeds the latest API CJ-4/SM, Cummins CES 20081, Volvo VDS-4, Mack EO-O Premium Plus (07), Caterpillar ECF-3, and Detroit Diesel Power Guard 93K218

Choice Heavy Duty 15W- 40 CJ-4 is a synthetic blend, heavy-duty multi- grade oil for all-season use in diesel powered or a mix of gasoline and diesel powered equipment. It meets or exceeds the warranty and service requirements of virtually all diesel and gasoline engine manufactures. It can be recommended for both newer and older engines. Choice Heavy Duty 15W- 40 CJ-4 is especially designed for today's high-performance, low-emissions diesel engines, equipped with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filters.

APPLICATIONS

Choice Heavy Duty 15W- 40 CJ-4 meets or exceeds all the following performance requirements:

- When CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF, CF-2 oils are required
- When SM, SL, SJ, SH, SG, SF oils are required
- When a US Military CID A-A-52306 performance level is required
- When MIL-L-210E/F oils performance level is required
- ACEA E5-02, JASO DHD-1, GLOBAL DHD-1
- When GM 4718M/6094M and Ford M2C153-E oils are required
- In all diesel and gasoline engines, including turbo-charged models
- In Detroit Diesel engines Power Guard Oil approval is required
- In Caterpillar engines ECF-3
- In Mack engines EO-O PREMIUM PLUS (07) approval, EO-N PREMIUM PLUS, EO-M Plus, EO-M, EO-L Plus, EO-L, EO-K/2
- In Cummins engines CES 20071, 20076, 20077, 20078, 20081
- In Volvo VDS-4, VDS-3, VDS-2 and VDS engines
- In Caterpillar drive trains TO- 32
- When Allison C-3/C-4 fluids are required
- Mercedes Benz MB 228.5, 228.3

Product Data Sheet

TYPICAL PROPERTIES

Test	Typical Results
Gravity, API	30
Viscosity	
cSt @ 40 °C	111
cSt @100 °C	15.5
Viscosity Index	146
Pour Point, °C	-32
Flash Point, °C	231
Borderline Pumping, °C	-20
Sulfated Ash wt%	1
Total Base Number	10
API Service	CJ-4, CI-4 Plus, CI-4, CH-4, CF-4, CF, CF-2, CE, CD-II/SM

HEALTH AND SAFETY INFORMATION

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet.