



FLEET CHARGE®

SCA PRECHARGED COOLANT / ANTIFREEZE

DESCRIPTION:

Fleet Charge SCA Precharged Coolant/Antifreeze is a Fully Formulated, ethylene glycol-based coolant, precharged with advanced technology Supplemental Coolant Additives (SCAs). Because it is SCA precharged, Fleet Charge SCA Precharged Coolant/Antifreeze requires no SCAs at initial fill and ensures proper chemistry at every top-off. Fleet Charge SCA Precharged Coolant/Antifreeze uses a low silicate and phosphate-free formulation.

BENEFITS:

- Works in ALL heavy-duty diesel, gasoline and natural gas engine cooling systems.
- Optimum protection against freezing and boil over.
- Provides corrosion protection of all cooling system metals and components.
- Incorporates nitrite to provide wet sleeve liner protection against cavitation.
- Designed to last the life of the engine when maintained with a high quality SCA filter system.
- Eliminates SCA mixing errors at initial fill.
- Phosphate free formula reduces the risk of scale.



Meets or exceeds these specification requirements:

- CATERPILLAR
- CUMMINS 90T8-4, CES 14603
- DETROIT DIESEL 7SE298, 93K217
- JOHN DEERE H24A1, H24C1
- NAVISTAR B-1 TYPE II
- FREIGHTLINER 48-22880
- VOLVO / MACK
- MTU 5048
- GM 1899M
- ASTM D4985
- ASTM D5345
- ASTM D6210
- TMC RP329

PROPERTIES:

	ASTM Test Method	Typical Values for Concentrate	
			50/50 Pre-Diluted
Specific Gravity 60/60	D1122	1.126	1.070
Freezing Point, 50% Vol.	D1177	-34°F (-37°C)	-34°F (-37°C)
Boiling Point, 50% Vol.	D1120	226°F (108°C)	226°F (108°C)
pH, 50 Vol. %	D1287	10.4	10.4
Reserve Alkalinity	D1121	7	3.5
Ash Content	D1119	1	<1
Color	—	Fuchsia	Fuchsia

FREEZE/BOIL PROTECTION CHART	% of Cooling System Capacity	PROTECTS FROM	
		Freezing Down to	Boiling Up to*
	50	-34°F	265°F
	60	-62°F	270°F
	70	-84°F	276°F

*Using a 15 PSI
Pressure Cap
at sea level.

CHEMISTRY THAT DRIVES COMMERCE™



FCAOB1
55 Gallon Concentrate Drum

UPC: 074804-03346-5



FCAB51
55 Gallon 50/50 Drum

UPC: 074804-02066-3



FCAOB3
1 Gallon Concentrate Bottle

Gallon UPC: 074804-00560-8

Case UPC: 074804-10560-5

Case SCC 14: 1-0074804-00560-5



FCAB53
1 Gallon 50/50 Bottle

Gallon UPC: 074804-00319-2

Case UPC: 074804-10319-9

Case SCC 14: 1-0074804-00319-9

FCAOB0
Bulk Concentrate

FCAB50
Bulk Concentrate

Part #	UNIT	Pack/Size	Case/Drum Dimensions	Unit Wt(lbs)	Units per Pallet	Pallets per Truck	Pallet Weight
FCAOB1	Drum	55 gal	23.5" dia. x 34.5"h	553.00	4	20	2,262
FCAB51	Drum	55 gal	23.5" dia. x 34.5"h	529.00	4	20	2,166
FCAOB3	Case	6/1 gal	16" l x 12.5" w x 12.5" h	60.00	36	20	2,210
FCAB53	Case	6/1 gal	16" l x 12.5" w x 12.5" h	57.00	36	20	2,102

(*) Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Material Safety Data available upon request.

To order, please call Old World Industries, LLC Customer Service at 1-800-323-8755.

PEAK Commercial & Industrial products have been trusted by fleets, large and small, for over 65 years, to keep their equipment running.



HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at www.peakauto.com, or by calling Old World Industries' PEAK technical support line at 1-800-477-5847. We Only Have One World...Please Help Protect It. All laws and regulations should be observed when disposing of Antifreeze/Coolant and Radiator Fluids. Call the EPA or the office of your state or local environmental agency for details on disposal procedures.



Old World
Industries, LLC

We Support
Be Car Care Aware
www.carcare.org

Distributed by Old World Industries, LLC Northbrook, IL 60062

p 800.323.5440 www.peakauto.com

©2015 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC. Long Life is a registered trademark of the Warren Distribution

RUN TRUE™