



MATERIAL SAFETY DATA SHEET

Choice Gear MP 80W-90 GL-5; 0001
MSDS PREPARATION DATE: 1/3/14

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Information

Product Name: Choice Gear MP 80W-90 GL-5
Product Description: Base Oil and Additives
Intended Use: Gear Oil
Product Code: 0001

Company Identification

Supplier: PetroChoice, Inc
P.O. Box 108
Defiance, PA 16633

Supplier General Contact Number: 1-800-437-1802
Emergency Number: Chemtrec 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines (see MSDS Section 15).

POTENTIAL HEALTH EFFECTS

Low order of toxicity. Excessive exposure may result in eye, skin, or respiratory irritation. High-pressure injection under skin may cause serious damage.

| | | | | | | |
|----------------------|---------------|---|---------------------|---|-------------------|---|
| NFPA RATINGS: | Health | 0 | Flammability | 1 | Reactivity | 0 |
| HMIS RATINGS: | Health | 0 | Flammability | 1 | Reactivity | 0 |

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Reportable Hazardous Substance(s) or Complex Substance(s)

| Name | CAS# | Concentration* |
|----------------|------------|----------------|
| OLEFIN SULFIDE | 68937-96-2 | 1 - 5% |

*All concentrations are percent by weight unless material is a gas.
Gas concentrations are in percent by volume.

SECTION 4: FIRST AID MEASURES

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SECTION 4: FIRST AID MEASURES (Continued)**SKIN CONTACT**

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

SECTION 5: FIRE FIGHTING MEASURES**EXTINGUISHING MEDIA**

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Sulfur Oxides, Aldehydes, Smoke, Fume, Oxides of Carbon, Incomplete Combustion Products

FLAMMABILITY PROPERTIES

Flash Point [Method]: >164°C (327°F) [ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

Autoignition Temperature: N/D

SECTION 6: ACCIDENTAL RELEASE MEASURES**NOTIFICATION PROCEDURES**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800) 424-8802.

SPILL MANAGEMENT

Land Spill: Stop leak if you can do it without risk. Recover by pumping or with suitable absorbent.

Water Spill: Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 6: ACCIDENTAL RELEASE MEASURES (Continued)

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7: HANDLING AND STORAGE

HANDLING

Prevent small spills and leakage to avoid slip hazard.

Static Accumulator: This material is a static accumulator.

STORAGE

Do not store in open or unlabelled containers. Keep away from incompatible materials.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS (standards for materials that can be formed when handling this product):

When mists / aerosols can occur, the following are recommended: 5 mg/m³ - ACGIH TLV, 10 mg/m³ - ACGIH STEL, 5 mg/m³ - OSHA PEL.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate.

Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable.

Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (Continued)

for your use conditions. Inspect and replace worn or damaged gloves.

The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data.

The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

See Sections 6, 7, 12, 13.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Typical physical and chemical properties are given below. Contact the Supplier for additional information.

GENERAL INFORMATION

| | |
|-----------------------|----------------|
| Physical State | Liquid |
| Color | Brown |
| Odor | Characteristic |
| Odor Threshold | N/D |

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

| | |
|--|---|
| Relative Density (at 15°C) | 0.899 |
| Flash Point [Method] | >164°C (327°F) [ASTM D-92] |
| Flammable Limits (Approximate volume % in air) | LEL: 0.9 UEL: 7.0 |
| Autoignition Temperature | N/D |
| Boiling Point / Range | > 316°C (600°F) |
| Vapor Density (Air = 1) | > 2 at 101 kPa |
| Vapor Pressure | < 0.013 kPa (0.1 mm Hg) at 20°C |
| Evaporation Rate (N-Butyl Acetate = 1) | N/D |
| pH | N/A |
| Log Pow (n-Octanol/Water Partition Coefficient) | > 3.5 |
| Solubility in Water | Negligible |
| Viscosity | 149.7 cSt (149.7 mm ² /sec) at 40°C 15.2 cSt (15.2 mm ² /sec) at 100°C |
| Oxidizing Properties | See Hazards Identification Section |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (Continued)
OTHER INFORMATION

| | |
|---|---------------|
| Freezing Point | N/D |
| Melting Point | N/A |
| Pour Point | -30°C (-22°F) |
| DMSO Extract (mineral oil only), IP-346 | < 3 %wt |

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION
ACUTE TOXICITY

| Route of Exposure | Conclusion / Remarks |
|---|---|
| Inhalation | |
| Toxicity (Rat): LC50 > 5000 mg/m ³ | Minimally Toxic. Based on test data for structurally similar materials. |
| Irritation: No end point data. | Negligible hazard at ambient/normal handling temperatures. Based on assessment of the components. |
| Ingestion | |
| Toxicity (Rat): LD50 > 5000 mg/kg | Minimally Toxic. Based on test data for structurally similar materials. |
| Skin | |
| Toxicity (Rabbit): LD50 > 5000 mg/kg | Minimally Toxic. Based on test data for structurally similar materials. |
| Irritation (Rabbit): Data available. | Negligible irritation to skin at ambient temperatures. Based on test data for structurally similar materials. |
| Eye | |
| Irritation (Rabbit): Data available. | May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. |

CHRONIC/OTHER EFFECTS
For the product itself:

Repeated and/or prolonged exposure may cause irritation to the skin, eyes, or respiratory tract. Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components or similar formulations.

SECTION 11: TOXICOLOGICAL INFORMATION (Continued)**Contains:**

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitizing in test animals.

Additional information is available by request.

The following ingredients are cited on the lists below: None.

| | | |
|--------------|-------------------------------|---------------|
| | --REGULATORY LISTS SEARCHED-- | |
| 1 = NTP CARC | 3 = IARC 1 | 5 = IARC 2B |
| 2 = NTP SUS | 4 = IARC 2A | 6 = OSHA CARC |

SECTION 12: ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material - Not expected to be harmful to aquatic organisms.

MOBILITY

Base oil component - Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY**Biodegradation:**

Base oil component - Expected to be inherently biodegradable

BIOACCUMULATION POTENTIAL

Base oil component - Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

SECTION 13: DISPOSAL CONSIDERATIONS (Continued)**EMPTY CONTAINER WARNING** (where applicable)

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14: TRANSPORT INFORMATION

LAND (DOT): Not Regulated for Land Transport

LAND (TDG): Not Regulated for Land Transport

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

AIR (IATA): Not Regulated for Air Transport

SECTION 15: REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD: When used for its intended purposes, this material is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

NATIONAL CHEMICAL INVENTORY LISTING: AICS, PICCS, KECI, ENCS, EINECS, TSCA, DSL, IECSC

EPCRA: This material contains no extremely hazardous substances.

SARA (311/312) REPORTABLE HAZARD CATEGORIES: None.

SARA (313) TOXIC RELEASE INVENTORY: This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

The Following Ingredients are Cited on the Lists Below: None.

--REGULATORY LISTS SEARCHED--

| | | | |
|---------------|------------------|-------------------|-------------|
| 1 = ACGIH ALL | 6 = TSCA 5a2 | 11 = CA P65 REPRO | 16 = MN RTK |
| 2 = ACGIH A1 | 7 = TSCA 5e | 12 = CA RTK | 17 = NJ RTK |
| 3 = ACGIH A2 | 8 = TSCA 6 | 13 = IL RTK | 18 = PA RTK |
| 4 = OSHA Z | 9 = TSCA 12b | 14 = LA RTK | 19 = RI RTK |
| 5 = TSCA 4 | 10 = CA P65 CARC | 15 = MI 293 | |

Code key: CARC=Carcinogen; REPRO=Reproductive

SECTION 16: OTHER INFORMATION**Disclaimer:**

The information and recommendations contained within this document are believed by PetroChoice to be accurate and reliable as of the date prepared. The information and recommendations are offered for the user's consideration and analysis and in no way guarantee the chemical specifications for the specified product. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense arising out of the product's improper use. The user should consider the information in this document in the context of how the selected product will be handled and used in conjunction with other products. It is the user's responsibility to determine that the product is suitable for the intended use.

Appropriate warnings and safe-handling procedures should be provided to all handlers and users. PetroChoice assumes no responsibility for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices within this document.